



# KC-1300



## Intelligent Media Converter Center Chassis

### Product Highlights:

- Supports 16 slots for hot-plug converters
- 19" rack mountable
- Supports -48VDC power input
- Power redundancy design
- Management
  - In-band console support
  - Web-based management
  - SNMP management
  - Telnet management
  - SNMP trap
- Load bearing up to 60kg

KC-1300 Intelligent Media Converter Center Chassis provides 16 slots for standalone media converters. A variety of optional media converts is provided and includes Gigabit copper to fiber and Fast Ethernet copper to fiber.

The chassis provides centered power supply to the installed media converters and serves as a converter center and wiring concentrator. The power system is featured with power redundancy for commercial AC and DC power input. For easy monitoring the media converter operation in each slot, KC-1300 also provides many network management interfaces including in-band console, telnet, web browsing, SNMP, and event SNMP trap for different application needs.

### Key Features:

- Managed Media Converter Center with 19-inch rack-mountable 2U chassis
- Managed system accommodates up to 16 media converters
- Highly modularized chassis design with
  - modular media converters
  - modular management module
  - two system power modules for power redundancy
- Provides high availability and maintainability
- Power backup (dual power inputs) featured with two power chassis
- Visible system status indication
- Supports in-band Telnet, SNMP and web-based management
- Supports out-of-band direct console management
- Management from anywhere and any platform using a web browser
- Easy-to-use point and click user interface
- Photographic quality interface to configure and monitor the system
- Supports in-band event SNMP trap report
- TFTP Software Upgrade

### Optional Media Converters

- Gigabit copper to Gigabit fiber converter
- Tri-speed 10/100/1000 copper to dual-speed fiber converter series
- 10/100 Fast Ethernet Copper to Fast Ethernet fiber converter series
- Multimode to single mode optical fiber media converter series

KC-300D



KGC-300



KGC-310M-C



KGC-311



KC-300DM



### Ordering Information:

Chassis	Slots	Managed	Power
KC-1300L-1A	16	None	1 AC
KC-1300L-2A	16	None	2 AC
KC-1300-1A	16	Yes	1 AC
KC-1300-2A	16	Yes	2 AC
KC-1300L-1D	16	None	1 DC
KC-1300L-2D	16	None	2 DC
KC-1300-1D	16	Yes	1 DC
KC-1300-2D	16	Yes	2 DC

### Specifications:

System Model	KC-1300-1A	KC-1300-2A	KC-1300-1D	KC-1300-2D
Management	Managed	Managed	Managed	Managed
System Model	KC-1300L-1A	KC-1300L-2A	KC-1300L-1D	KC-1300L-2D
Management	Unmanaged	Unmanaged	Unmanaged	Unmanaged
LEDs	Power1, Power2, CPU status, Fan status, Console Rx status, pork link status			
Number of Power	1 AC power	2 AC power	1 DC power	2 DC power
Input Voltage	100-240VAC	100-240VAC	48VDC	48VDC
Power Supply	70W	70W	75W	75W
19" Rack Mount	Yes	Yes	Yes	Yes
Number of MC Slots	16	16	16	16

### Mechanical:

Chassis Height (2U)	88mm	88mm	88mm	88mm
Dimension	443x88x300 mm	443x88x300 mm	443x88x300 mm	443x88x300 mm
Load Bearing	60kg	60kg	60kg	60kg
Weight	5.5kg	6.2kg	5.5kg	6.2kg

(with 1 or 2 AC power, management module and no MC converters)

### Environmental:

Operating Temperature	-5°C ~ 40°C
Storage Temperature	-20°C ~ 80°C
Relative Humidity	5% ~ 90% non-condensing
Approval	FCC Class A, VCCI Class A, CE mark Class A, IEC 60950-1 safety

### Information of Optional Standalone Media Converters:

KC-300D	10/100Base-TX to 100Base-FX media converter series
KC-300DM	10/100Base-TX to 100Base-FX media converter series with remote loopback test and remote TP link monitoring functions
KGC-300	1000Base-T to 1000Base-X media converter series
KGC-310M-C	Managed 10/100/1000Base-T to dual-speed fiber media converters
KGC-311	Multimode to single mode optical fiber media converter series



**Katron Technologies Inc.**  
 15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd.,  
 Hsi-chih District, New Taipei City, Taiwan  
 Tel: 886-2-2698-3878  
 Fax: 886-2-2698-3873  
 E-mail: kti@ktinet.com.tw  
 URL: http://www.ktinet.com.tw

Trademarks: All brand names are trademarks or registered trademarks of their respective holders.  
 This information is subject to change without prior notice.