

NV-2400H

24-Port VDSL2 IP DSLAM

NV-2400H is a compact 24-port VDSL2 IP DSLAM with 2 Gigabit Ethernet Combo interfaces and built-in POTS/ISDN splitter. It is compliant to ITU-T G.993.2 standard and supports VDSL2 30a profile that features 100 Mbps of symmetric data rate over the existing copper wires. NV-2400H is an ideal choice for ISPs and System Integrators that are looking for a high performance broadband solution for their triple play applications.

It offers a user-friendly management interface that allows service providers to monitor and control their services in a highly secure and efficient way. With many powerful and advanced features, this Mini IP DSLAM is the perfect solution for deploying broadband access, IP Surveillance, Hospitality and MTU/MDU applications.

Features

- 1.5 U design, 24 VDSL2 ports with POTS/ISDN splitter
- Supports VDSL2 profile 30a
- Supports IEEE 802.1q tagging VLAN with Q-IN-Q
- Supports up to 100 Mbps symmetric

- Supports interleavedelay for noise resistant and data loss.
- Supports traffic classification QoS, TOS and DSCP
- Supports Jumbo packet up to 9k byte
- Bandwidth management (Rate Control)

Specifications

Interface	2 x RJ-21 connector for 24 x VDSL2 ports/POTS 2 x Copper/Fiber combo giga port 1 x console port(RJ-45/115200bps) 1x RJ-45 Alarm port for 4 Alarm inputs
Indicators	System:PWR Gigabit Port: LINK/ACT/Speed/Collision Alarm: Run VDSL2: LINK

Standards VDSL2 ITU-T G993.2 up to VDSL2 profile 30a IEEE 802.3/802.3u/802.3ab/802.3z IEEE 802.1q VLAN Tag Base(Q in Q) IEEE 802.1d Spanning Tree Protocol(STP)

Protocols	IGMP Snooping/Proxy v1, v2 and v3
	Multicast MAC address mapping
	Up to 512 Multicast Channels
	Fast and Normal Leave Modes
Power Consumption	90 Wattsmaximum
Dimensions	435 x 260 x 67 mm (17.13" x 10.24" x 2.64")
Temperature	-10°~50°C (Operating), -40°~70°C (Storage)
Humidity	5 - 95% non-condensing
Certification	CE, FCC, RoHS Compliant
Chipset	Metanoia

Application



Switch

Ordering Information

Model Name Description
NV-2400H 24-port VDSL2 IP DSLAM

sales@netsys.com.tw



^{*}Netsys reserves the right to change specifications without prior notice